

EPOCA Tempo Stripe Tempo Stripe 500 Recycled polyamide 6 - Ecotrust 350 gr, 100% recycled Tæppefliser og -planker - Technical Details

Weight: 500 g/m²

Material: Recycled polyamide 6

Structure: Tufted loop pile

Backing: Ecotrust 350 gr, 100% recycled

DESCRIPTION	METHOD	DATA
-------------	--------	------

KONSTRUKTION

Struktur	ISO 2424	Tuftet loop pile
Gauge	ISO 2424	1/10
Luvmateriale	Regulation (EU) No 1007/2011	Recycled polyamide 6
Farvemethode	-	Forfarvet garn
Bagside	ETL	Ecotrust 350, 100% recycled
Dimensioner	ISO 3018	48x48/96x96
Totalhøjde	ISO 1765	Ca. 7,0 mm.
	.	0.28 "
Slidlag	ISO 1766	Ca. 3,0 mm.
Noppeantal	ISO 1763	Ca. 161.500 pr.m2
Totalvægt	ISO 8543	Ca. 2.525 g/m2
	.	70.8 oz./yd2
Luvindsatsvægt	ETL	500 g/m2
	.	14.75 oz./yd2
Luvdensitet	ISO 8543.	Ca. 0,100 g/cm3

EGNETHEDSPRØVNINGER

Brugsområder	EN 1307	33 - Erhverv - Kraftig brug
TGA	TGA Certificate	Nr.TGA.2025/001
Brugsområder	Gulvbranchen	Klasse 33
Rullehjulsegnet	EN 985	Ja, konstant brug

Trappegnet	EN 1963	Ja
Antistatiske egenskaber	ETL	Permanent antistatisk
Personopladning	ISO 6356	Antistatisk
Trinlydsdæmpning	ISO 717-2	25 dB
Akustisk absorption	ISO 354	0,25 aW
Isoleringsevne	ETL	Ca. 0,12 m2K/W
Lysrefleksion	ETL	Testrapport
Lysægthed	ISO 105-B02	>5
	AATCC 16	5.0
Gnideægthed våd	ISO 105-X12	>3
	AATCC 165	5.0
Gnideægthed tør	ISO 105-X12	>3-4
	AATCC 165	5.0
Vandægthed mønstrede/melerede	ISO 105-E01	>4
Cleaning	AATCC 138	5.0
Colour fast.Oxides of nitrogen	AATCC 164	5.0
Øvrige brugstests	ASTM D5252 Hexapod	3.5/3.5
	AATCC 134 Electrost.propensity	2.0 kV

SIKKERHED & MILJØ

Brandklassifikation	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass
	EN 13501-1 Euroclass	Bfl-s1
CE Mærkning	EN 14041	Certificeret
	CPR	1021-CPR-010-1/16
	Ydeevnedeklaration	DOP 5B-PA-ECT350

	Notified body no.	1021
	Ce Year	12
	Content of PCP	DL
	Formaldehyde emission	NA
	Skridsikkerhed	Class DS
Indeklima	Green Label Plus	Godkendt
	METS Report	Pass
	Emissions dans l'air intérieur	A+/A+
	Indoor Air Comfort Gold	Group 3
	ABG	ABG-28-01-03-03-2018
Miljø	BASTA	Registreret
	Byggvarubedömningen ID	54078 (ECTA)
	SundaHus score	B (ECTA)
	BREEAM International	Godkendt
	BREEAM International	Godkendt
	BREEAM-NOR	Godkendt
	EPD	EPD-IES-0009104
	C2C Certified Full Scope	Bronze, Version 4.0
	Recycled Content, ISO 14021	Ca. 49,0 %
	Recycled Content for LEED	Ca. 44,0 %
	GWP Cradle to Gate (A1-A3)	5,00 KgCO ₂ eq/m ²

PRODUCENT

Fabrikscertificering	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	ISO 45001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK