

EPOCA Tempo Stripe Tempo Stripe 500 Recycled polyamide 6 - Woven textile Væg-til-væg - Technical Details

Weight: 500 g/m²

Material: Recycled polyamide 6

Structure: Tufted loop pile

Backing: Woven textile

DESCRIPTION	METHOD	DATA
-------------	--------	------

KONSTRUKTION

Struktur	ISO 2424	Tuftet loop pile
Gauge	ISO 2424	1/10
Luvmateriale	Regulation (EU) No 1007/2011	Recycled polyamide 6
Farvemethode	-	Forfarvet garn
Bagside	ETL	WT - Vævet tekstil
Dimensioner	ISO 3018	Approx. 400 cm
Totalhøjde	ETL	Ca. 5,5 mm.
	.	0.28 "
Slidlag	ETL	Ca. 2,5 mm.
Totalvægt	ISO 8543	Ca. 2.200 g/m ²
	.	64.9 oz./yd ²
Luvindsatsvægt	ETL	500 g/m ²
	.	14.75 oz./yd ²

EGNETHEDSPRØVNINGER

Brugsområder	EN 1307	33 - Erhverv - Kraftig brug
Rullehjulseget	ETL	Ja, konstant brug
Trappeget	ETL	Ja
Antistatiske egenskaber	ETL	Permanent antistatisk
Trinlydsdæmpning	ISO 717-2	24 dB
Akustisk absorption	ISO 354	0,20 aW

Isoleringsevne	ETL	Ca. 0,09 m2K/W
Lysrefleksion	ETL	Testrapport
Lysægthed	AATCC 16	5.0

SIKKERHED & MILJØ

Brandklassifikation	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass
	EN 13501-1 Euroclass	Bfl-s1
CE Mærkning	EN 14041	Certificeret
	CPR	1021-CPR-006-1/16
	Ydeevnedeklaration	DOP 1B-PA-WT
	Notified body no.	1021
	Ce Year	12
	Content of PCP	DL
	Formaldehyde emission	NA
	Skridsikkerhed	Class DS
Indeklima	Green Label Plus	Godkendt
	Indoor Air Comfort Gold	Group 3
	ABG	ABG-28-01-03-03-2018
Miljø	BASTA	Registreret
	Byggvarubedömningen ID	146841 (WTA)
	SundaHus score	B (WTA)
	BREEAM International	Godkendt
	EPD	EPD-IES-0009105
	C2C Certified Full Scope	Bronze, Version 4.0
	GWP Cradle to Gate (A1-A3)	4,44 KgCO2eq/m2

PRODUCENT

Fabrikscertificering	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	ISO 45001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK