

EPOCA Tempo Tempo 500 Recycled polyamide 6 - Ecotrust 350 gr, 100% recycled Tæppefliser og -planker - Technical Details

Weight: 500 g/m²

Material: Recycled polyamide 6

Structure: Tufted loop pile

Backing: Ecotrust 350 gr, 100% recycled

DESCRIPTION	METHOD	DATA
-------------	--------	------

KONSTRUKTION

Struktur	ISO 2424	Tuftet loop pile
Gauge	ISO 2424	1/10
Luvmateriale	Regulation (EU) No 1007/2011	Recycled polyamide 6
Farvemethode	-	Forfarvet garn
Bagside	ETL	Ecotrust 350, 100% recycled
Dimensioner	ISO 3018	48x48/96x96/24x96cm
Totalhøjde	ISO 1765	Ca. 7,0 mm.
	.	0.28 "
Slidlag	ISO 1766	Ca. 3,0 mm.
Noppeantal	ISO 1763	Ca. 161.500 pr.m2
Totalvægt	ISO 8543	Ca. 2.525 g/m2
	.	70.8 oz./yd2
Luvindsatsvægt	ETL	500 g/m2
	.	14.75 oz./yd2
Luvdensitet	ISO 8543.	Ca. 0,100 g/cm3

EGNETHEDSPRØVNINGER

Brugsområder	EN 1307	33 - Erhverv - Kraftig brug
TGA	TGA Certificate	Nr.TGA.2025/001
Brugsområder	Gulvbranchen	Klasse 33
Rullehjulseget	EN 985	Ja, konstant brug

Trappegnet	EN 1963	Ja
Antistatiske egenskaber	ETL	Permanent antistatisk
Personopladning	ISO 6356	Antistatisk
Trinlydsdæmpning	ISO 717-2	25 dB
Akustisk absorption	ISO 354	0,25 aW
Isoleringsevne	ETL	Ca. 0,12 m2K/W
Lysrefleksion	ETL	Testrapport
Lysægthed	ISO 105-B02	>5
	AATCC 16	5.0
Gnideægthed våd	ISO 105-X12	>3
	AATCC 165	5.0
Gnideægthed tør	ISO 105-X12	>3-4
	AATCC 165	5.0
Vandægthed ensfarvede	ISO 105-E01	>3-4
Cleaning	AATCC 138	4.5
Colour fast.Oxides of nitrogen	AATCC 164	5.0
Øvrige brugstests	ASTM D5252 Hexapod	2.5/3.0
	AATCC 134 Electrost.propensity	2.3 kV

SIKKERHED & MILJØ

Brandklassifikation	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass
	EN 13501-1 Euroclass	Bfl-s1
	ASISO 9239.1-2003	8,80 KW/m2
CE Mærkning	EN 14041	Certificeret
	CPR	1021-CPR-010-1/16

	Ydeevnedeklaration	DOP 5B-PA-ECT350
	Notified body no.	1021
	Ce Year	09
	Content of PCP	DL
	Formaldehyde emission	NA
	Skridsikkerhed	Class DS
Indeklima	BASTA	Registreret
	Green Label Plus	Godkendt
	METS Report	Pass
	Emissions dans l'air intérieur	A+/A+
	Indoor Air Comfort Gold	Group 3
	ABG	ABG-28-01-03-03-2018
Miljø	BASTA	Registreret
	Byggvarubedömningen ID	54078 (ECTA)
	SundaHus score	B (ECTA)
	BREEAM International	Godkendt
	BREEAM-NOR	Godkendt
	EPD	EPD-IES-0009104
	C2C Certified Full Scope	Bronze, Version 4.0
	Recycled Content, ISO 14021	Ca. 49,0 %
	Recycled Content for LEED	Ca. 44,0 %
	LEED V4	Qualified
	GWP Cradle to Gate (A1-A3)	5,00 KgCO2eq/m2

PRODUCENT

Fabrikscertificering	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC

ISO 45001	Audited and verified by BVC
CRuk	Member of Carpet Recycling UK