

RESIDENTIAL Cantana Luna - Væg-til-væg - Technical Details

Weight: 775 g/m²

Material: 100% polypropylene

Structure: Tufted loop pile

Backing: High latex foam

DESCRIPTION	METHOD	DATA
-------------	--------	------

KONSTRUKTION

Struktur	ISO 2424	Tuftet loop pile
Gauge	ISO 2424	5/32
Luvmateriale	Regulation (EU) No 1007/2011	100% polypropylene
Farvemetode	-	Forfarvet garn
Bagside	ETL	HL - High foam
Dimensioner	ISO 3018	Approx. 400/500 cm
Totalhøjde	ETL	Ca. 9,0 mm.
Slidlag	ETL	Ca. 4,0 mm.
Noppeantal	ETL	Ca. 75.600 pr.m2
Totalvægt	ISO 8543	Ca. 2.700 g/m2
Luvindsatsvægt	ETL	775 g/m2
Luvdensitet	ETL	Ca. 0,130 g/cm3

EGNETHEDSPRØVNINGER

Brugsområder	ETL	23 - Bolig - Kraftig brug
Garanti mod pletter og slid	ETL	10 år
Antistatiske egenskaber	ETL	Permanent antistatisk
Trinlydsdæmpning	ETL	33 dB
Isoleringsevne	ETL	Ca. 0,16 m2K/W

SIKKERHED & MILJØ

Brandklassifikation	EN 14041	Efl
---------------------	----------	---------------------

CE Mærkning	EN 14041	Certificeret
	Ydeevnedeklaration	DOPE
	Notified body no.	NA
	Ce Year	25
	Content of PCP	DL
	Formaldehyde emission	NA
	Skridsikkerhed	Class DS
Indeklima	Indoor Air Comfort Gold	Group 15

PRODUCENT

Fabrikscertificering	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	ISO 45001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK