

RESIDENTIAL Keflavik Keflavik 620 100% wool - Weaving latex Væg-til-væg - Technical Details

Weight: 620 g/m²

Material: 100% wool

Structure: Woven loop pile

Backing: Weaving latex



23 - Bolig - Kraftig brug



Permanent antistatisk



Efl



Certificeret

DESCRIPTION	METHOD	DATA
-------------	--------	------

KONSTRUKTION

Struktur	ISO 2424	Vævet loop pile
Luvmateriale	Regulation (EU) No 1007/2011	100% uld
Farvemetode	-	Yarn dyed
Bagside	ETL	WL - Weaving latex
Dimensioner	ISO 3018	Approx. 400/500 cm
Totalhøjde	ETL	Ca. 5,8 mm.
Totalvægt	ISO 8543	Ca. 2.325 g/m2
Luvindsatsvægt	ETL	620 g/m2

EGNETHEDSPRØVNINGER

Brugsområder	ETL	23 - Bolig - Kraftig brug	
Antistatiske egenskaber	ETL	Permanent antistatisk	
Personopladning	ISO 6356	Antistatisk	
Lysægthed	ISO 105-B02	>4	
Gnideægthed våd	ISO 105-X12	>3	
Gnideægthed tør	ISO 105-X12	>3-4	
Vandægthed ensfarvede	ISO 105-E01	>3-4	

SIKKERHED & MILJØ

Brandklassifikation	EN 14041	Efl	
---------------------	----------	---------------------	--

CE Mærkning	EN 14041	Certificeret	
	Ydeevnedeklaration	DOPE	
	Notified body no.	NA	
	Ce Year	23	
	Content of PCP	DL	
	Formaldehyde emission	NA	
	Skridsikkerhed	Class DS	

PRODUCENT

Fabrikscertificering	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	ISO 45001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK