

# Actus 6.0 HDF

2-layer engineered plank



Cfl-s1



|                               |                                                                           |
|-------------------------------|---------------------------------------------------------------------------|
| Dimension                     | 500*70*11,5 mm                                                            |
| Top layer                     | approx. 6 mm                                                              |
| Composition                   | HDF, Hardwood cover lamella                                               |
| Laying pattern                | Brick pattern, Herringbone                                                |
| Package size                  | 2,1 m <sup>2</sup>                                                        |
| Pallet size                   | 100,8 m <sup>2</sup> / 48 packages                                        |
| Weight                        | approx. 7,0 kg / m <sup>2</sup>                                           |
| Surface                       | Oil, Matt lacquer                                                         |
| Types of wood                 | Oak, Smoked oak                                                           |
| Slip resistance               | Lacquer R10, Oil R10, Oil brushed R11                                     |
| Profile                       | bevelled tongue and groove(r+l)                                           |
| Installation                  | Full-surface bonding                                                      |
| Adhesive                      | Parafix Classic                                                           |
| Underfloor heating            | Suitable for warmwater underfloor heating                                 |
| Thermal resistance            | 0,0620 m <sup>2</sup> K/W                                                 |
| Fire class                    | Cfl-S1                                                                    |
| Sustainability & certificates | PEFC, ISO 14001, ISO 38200, eco-Institut, Building authority approval, CE |
| Origin wood (oak)             | Europe                                                                    |
| Production                    | Austria                                                                   |
| Cleaning & maintenance        | According to instructions                                                 |