

# TECHNICAL DATASHEET

Home Laminate Flooring

10/32 LONG

Coreboard		HDF swell stopp plus
Profile		The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use	<b>32</b>	
European Norm EN13329	 EN 13329-32	
Format	<b>LONG</b>	
Dimension mm (length x width)	<b>2050 x 245</b>	
Complete thickness	<b>10</b>	
Thickness of silenizio® special cellulose		
Bevel	<b>WV4</b>	
Pallet	<b>Packaging</b>	
Paket information	<b>Euro</b>	
	Piece	5
	m2	2,51
	kg	23,34
Pallet information		
	Piece	165
	m2	82,83
	kg	790,00
	<b>Classification and general requirements according EN13329</b>	
Abrasion resistance according EN13329, annex E	AC4 (IP ≥ 4000)	
Impact resistance according EN13329, annex H	Big ball: ≥ 750 mm Small ball: ≥ 12 N	
Resistance to staining EN438	Group 1 + 2: level 5 group 3: level 4	
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact	
Effect of a castor chair according EN425 (Type W)	No change in appearance or damage	
Thickness swelling according ISO 24336	≤ 18 %	
Tolerance of top layer according EN13329	length ± 0,3 mm width ± 0,1 mm thickness ± 0,5 mm	
Light fastness according EN13329	grey scale ≥ level 4 (EN:20105-A02)	
Static indentation by constant pressure according EN ISO 24343-1	< 0,05	
Surface soundness according EN13329, annex D	≥ 1,25 N/mm2	
Thermal resistance according to EN 12667	0,08 m² K/W	

