

ECO Mineral - Væg-til-væg WT - Technical Details

Weight: 540 g/m²

Material: Recycled polyamide 6

Structure: Woven loop pile

Backing: Woven textile

DESCRIPTION

METHOD

DATA

KONSTRUKTION

Struktur	ISO 2424	Vævet loop pile
Luvmateriale	Regulation (EU) No 1007/2011	Recycled polyamide 6
Farvemethode	-	Continue farvet
Bagside	ETL	WT - Vævet tekstil
Dimensioner	ISO 3018	Approx. 400 cm
Totalhøjde	ISO 1765	Ca. 4,0 mm.
Totalvægt	ISO 8543	Ca. 2.250 g/m2
Luvindsatsvægt	ETL	540 g/m2
	.	15,87 oz./yd2

EGNETHEDSPRØVNINGER

Brugsområder	EN 1307	33 - Erhverv - Kraftig brug
Rullehjulseget	EN 985	Ja, konstant brug
Trappeget	EN ISO 12951	Ja
Antistatiske egenskaber	ETL	Permanent antistatisk
Personopladning	ISO 6356	Antistatisk
Trinlydsdæmpning	ISO 717-2	17 dB
Akustisk absorption	ISO 354	0,15 aW
Isoleringsevne	ETL	Ca. 0,07 m2K/W
Lysrefleksion	ETL	Testrapport
Lysægthed	ISO 105-B02	>5

	AATCC 16	5.0
Gnideægthed våd	ISO 105-X12	>3
Gnideægthed tør	ISO 105-X12	>3-4
Vandægthed ensfarvede	ISO 105-E01	>3-4

SIKKERHED & MILJØ

Brandklassifikation	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass
	EN 13501-1 Euroclass	Cfl-s1
CE Mærkning	EN 14041	Certificeret
	CPR	1021-CPR-006-2/16
	Ydeevnedeklaration	DOP 1C-PA-WT
	Notified body no.	1021
	Ce Year	22
	Content of PCP	DL
	Formaldehyde emission	NA
	Skridsikkerhed	Class DS
Indeklima	Green Label Plus	Godkendt
	Indoor Air Comfort Gold	Group 14
Miljø	Byggvarubedömningen ID	164084
	BREEAM International	Godkendt
	EPD	MD-24054-EN
	C2C Certified Full Scope	Bronze, Version 4.0
	Recycled Content, ISO 14021	Ca. 24,0 %
	Recycled Content for LEED	Ca. 18,0 %
	GWP Cradle to Gate (A1-A3)	5,80 KgCO2eq/m2

PRODUCENT

Fabrikscertificering	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	ISO 45001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK