



Linoleum floor to click with HDF core board

Technical Data	
Plank format	620 x 450 x 10 mm
Packaging unit	6 planks/1,68 m ²
Palette content	60 cartons/100,80 m ²
Surface	X-treme finish sealing
Top layer	2,0 mm double layer linoleum
Carrier board	6,8 mm HDF
Underlay	1,2 mm Pressed cork impact sound insulation
Edge processing	4-side flat
Laying method	Glueless UNICLIC technique
Testing Values	
Electrostatic propensity (EN 1815)	< 2 kV
Resilient flooring classification (EN 685)	23/32
Determination of burning behaviour (EN-ISO 9239-1)	Cfl-s1 • Does not release toxic gas during combustion
Resistance to chemicals (EN 423)	Resistant to diluted acids, oils, fats, etc.
Moisture proof	No
Mass per unit area (EN 430)	8.600 g/m ²
Suitable for underfloor heating	Yes (Hot water underfloor heating)
Residual indentation (EN 433)	0,12 mm
Slip retardant (DIN 51130 • EN 13893)	DIN = R 10 • EN = DS > 0,30
Suitable for caster chairs (EN 425 • EN 12529)	Yes, with casters type W
Impact sound reduction (EN-ISO 717-2 • DIN 52210-030 E1-T-PFLD)	16 dB
Thermal conductivity (DIN-EN 52612-Teil 1)	0,098 m ² x K/W
Resistance to stubbed and burning cigarettes (EN 1399)	Yes
Disposal	Household waste or Second Life



Regularly Emission tested under test chamber-conditions according to DIN ISO 16000-9 and DIN EN 717-1 i.A.

