

CLUB Texture 2000 - Væg-til-væg WT - Technical Details

Weight: 2000 g/m²

Material: Recycled polyamide 6

Structure: Tufted cut pile

Backing: Woven textile

DESCRIPTION

METHOD

DATA

KONSTRUKTION

Struktur	ISO 2424	Tuftet cut pile
Gauge	ISO 2424	1/8
Luvmateriale	Regulation (EU) No 1007/2011	Recycled polyamide 6
Farvemetode	-	Continue farvet
Bagside	ETL	WT - Vævet tekstil
Dimensioner	ISO 3018	Approx. 400 cm
Totalhøjde	ISO 1765	Ca. 15,5 mm.
	.	0.61 "
Slidlag	ISO 1766	Ca. 13,0 mm.
Noppeantal	ISO 1763	Ca. 196.000 pr.m2
Totalvægt	ISO 8543	Ca. 3.550 g/m2
	.	104.73 oz./yd2
Luvindsatsvægt	ETL	2.000 g/m2
	.	59 oz./yd2
Luvdensitet	ISO 8543.	Ca. 0,140 g/cm3

EGNETHEDSPRØVNINGER

Brugsområder	EN 1307	33 - Erhverv - Kraftig brug
	Gulvbranchen	Klasse 33
Antistatiske egenskaber	ETL	Permanent antistatisk
Personopladning	ISO 6356	Antistatisk

Trinlydsdæmpning	ISO 717-2	36 dB
Akustisk absorption	ISO 354	0,30 aW
Isoleringsevne	ETL	Ca. 0,27 m2K/W
Lysrefleksion	ETL	Testrapport
Lysægthed	ISO 105-B02	>5
	AATCC 16	4.0
Gnideægthed våd	ISO 105-X12	>3
	AATCC 165	5.0
Gnideægthed tør	ISO 105-X12	>3-4
	AATCC 165	5.0
Vandægthed ensfarvede	ISO 105-E01	>3-4
Cleaning	AATCC 138	5.0
Colour fast.Oxides of nitrogen	AATCC 164	3.5
Øvrige brugstests	ASTM D5252 Hexapod	4.0/ 3.5
	-	Commercial - Heavy
	AATCC 134 Electrost.propensity	2,9 kV

SIKKERHED & MILJØ

Brandklassifikation	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass
	EN 13501-1 Euroclass	Cfl-s1
	ASISO 9239.1-2003	3,30 KW/m2
CE Mærkning	EN 14041	Certificeret
	CPR	1021-CPR-006-2/16
	Ydeevnedeklaration	DOP 1C-PA-WT
	Notified body no.	1021

	Ce Year	12
	Content of PCP	DL
	Formaldehyde emission	NA
	Skridsikkerhed	Class DS
Indeklima	Green Label Plus	Godkendt
	Emissions dans l'air intérieur	A+/A+
	Indoor Air Comfort Gold	Group 7
	ABG	ABG-28-02-07-01-2018
Miljø	BASTA	Registreret
	Byggvarubedömningen ID	148293
	SundaHus score	B
	BREEAM International	Godkendt
	EPD	EPD-IES-0020165
	C2C Certified Full Scope	Bronze, Version 4.0
	Recycled Content, ISO 14021	Ca. 3,0 %
	Recycled Content for LEED	Ca. 3,0 %
	LEED	Qualified
	GWP Cradle to Gate (A1-A3)	7,74 KgCO2eq/m2

PRODUCENT

Fabrikscertificering	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	ISO 45001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK