

Wood Floor Glue

Technical datasheet.

BERRY  ALLOC

1. Product information

Product Ref. : 63003597 - contents : 3 bags of 7,5kg.

The BerryAlloc Wood Floor glue is 1 component adhesive, ready to use.

Tested on solid oak according to NF B54 008 - report FCBA. Suitable for all floorings that comply with the EN 13489 standard.



2. Use of product

Working time at 23°C and 50% R.H. : 30 minutes (Walkable after 24h).

Temperature product when applying : Minimum +15°C.

Use in well-ventilated rooms. Good ventilation is important during application and curing of the product.

It is recommended to carry out tests on every surface before use.

The user needs to make sure that the product is suitable for the application. Consult our technical service if necessary. Remove irregularities such as old adhesive residues mechanically. Preferably roughen/sand smooth surfaces to increase the contact surface. Uneven floors should be levelled first using a levelling layer. Any cracks or damages must be repaired with synthetic mortar. Cementitious screeds with high residual moisture have to be treated. If the screed is in extremely poor condition, it must be removed and replaced.

Existing ceramic, granite, marble or similar floors should be properly degreased and then mechanically scratched. In case of rising damp or highly absorbent surfaces, the subfloor must be treated with a primer.

In any case, do not apply a moisture barrier to screeds with underfloor heating, any residual moisture present will have to be removed by switching on the heating system, prior to installation.

We refer to our installation manuals of the BerryAlloc wood products for more information.

3. Areas of application

The product should be applied directly to the substrate with the coarsely serrated adhesive trowel provided. The adhesive must be spread evenly over the entire surface.

The flooring could be slightly loaded to ensure perfect spread of the adhesive.

Suitable for bonding flooring on subfloors with underfloor heating.

Any adhesive that may protrude along the edges can be removed using a stopping knife. Adhesive residue that has not yet dried, can be removed using our **Cleaning Wipes (9310-0023)**.

Caution : After curing remove mechanically.

4. Technical data

Type of product : Hybrid polymer

Solvent, water, isocyanate and phthalate free

French VOC emission class A+

FCBA - Glue for parquet behavior according to NF B 54008 standard

